04-02_CONTROL BOX (PPA-GF)-ENG.DOC

CONTROL BOX

MOULDED MATERIAL	-PPA+GF-(Poliarilammide+glass fiber)
FAMILY OF MATERIALS	-PPA; PAA;PAMXD6;PARA(High Performance Polyamides)
POLYMER'S FEATURES	Compared to typical nylons, PPA has higher thermal properties and it is stronger, stiffer and less sensitive to moisture. It retains its excellent mecha properties – including fatigue and creep resistance – over a broad temperat range in moist and chemically aggressive environments. Key Features Higher strength and stiffness at elevated temperatures Better retention of mechanical properties in high humidity Greater resistance to a broader range of chemicals PPA boasts heat deflection temperatures (HDT), up to 310°C (590°F), mal possible to withstand the high reflow temperatures of SMT processing with blistering or warping. Continuous use temperatures from 120 to 185°C (248-365°F) make resin a reliable choice for demanding under-the-hood automotive components. Retains Mechanical Properties in Humid Environments Humid environments can have a devastating effect on the mechanical prop of typical nylons. PPA's lower water absorption results in significantly bette retention of strength and stiffness properties, even with high levels of humid PPA's highly aromatic ring structure provides greater resistance to more chemicals than typical nylons, even at high temperatures. This allows it to to used in demanding automotive and industrial applications, where it must withstand prolonged exposure to aggressive chemicals .such as: Bio-diesel fuel -Brake fluid -Calcium chloride -Glycols -Synthetic motor oil - salt -Sulfuric acid -Transmission fluid -Zinc chloride
APPLICATION FIELDS	Automotive Air inlet Body/structural components Electrical and electronic components Feed systems Heating and cooling Lighting systems Transmission/transmission components
SPECIAL NOTES	Cattini Engineering Plastics is recommended by: SOLVAY Advanced Polymers : www.solvayadvancedpolymers.com

CATTINI S.R.L. - via Giuseppe Verdi, 4 - 42018 San Martino in Rio (RE) ITA Tel.: +39 0522 695 220 Fax: +39 0522 695 254 web: http://www.cattini.it Certificata: UNI EN ISO 9001 - UNI EN ISO 14001