01-04\_CONNECTOR-2(PEEK)-ENG.DOC

MOULDED MATERIAL	PEEK
FAMILY OF MATERIALS	PAEK ; PEEK ; PEK ; PEEEK ; PEKK ; PEKEKK (Polyariletherketone)
POLYMER'S FEATURES	<ul> <li>combination of mechanical properties, temperature resistance and chemical resistance that make it the best known among the so called «advanced plastic materials».</li> <li>High maximum usage temperature in the air (250°C continuous temperature, up to 310°C for short period)</li> <li>High mechanical resistance, creep stiffness and hardness, also at high temperatures</li> <li>Excellent chemical and hydrolysis resistance</li> <li>Good dimensional stability</li> <li>Low intrinsic flammability and very low flue gas emission during the combustion process</li> <li>Good dielectric properties and electrical isolation (except for carbon-filled PEEK)</li> <li>Excellent resistance to strong energy radiations (gamma and X-rays)</li> <li>low viscosity which allows to create assembly without fasteners</li> <li>In accordance to EU and FDA directives, concerning materials being contact to food substances.</li> <li>These features, if they refer to plastics used in contact with food product added to his excellent sterizability through steam, dry heat, ethylen oxida and gamma rays make this product particularly appreciated for medical, pharmaceutical and food applications.</li> </ul>
APPLICATION FIELDS	Any fields where high performance polymers are needed, or in the production of components with minimum thickness and the need to maintain flexibility and dimensional stability with temperature extremes. Cattini Engineering Plastics is recommended by: - VICTREX® : http://victrex.com -

CONNECTOR

CATTINI S.R.L. - via Giuseppe Verdi, 4 - 42018 San Martino in Rio (RE) ITA Tel.: +39 0522 695 220 Fax: +39 0522 695 254 web: http://www.cattini.it Certificata: UNI EN ISO 9001 - UNI EN ISO 14001