

STERILANT TANK



MOULDED MATERIAL	PEEK-GF (fiber glass)
FAMILY OF MATERIALS	PAEK ; PEEK ; PEK ; PEEKK ; PEKK ; PEKEKK (Polyariletherketone)
POLYMER'S FEATURES	<p>VICTREX® PEEK materials are based on the polyeteretherketone resin. This high technology semi crystalline thermoplastic has a unique combination of mechanical properties, temperature resistance and chemical resistance that make it the best known among the so called «advanced plastic materials».</p> <ul style="list-style-type: none"> – High maximum usage temperature in the air (250°C continuous temperature, up to 310°C for short period) – High mechanical resistance, creep stiffness and hardness, also at high temperatures – Excellent chemical and hydrolysis resistance – Excellent friction and wear resistance – Good dimensional stability – Low intrinsic flammability and very low flue gas emission during the combustion process – Good dielectric properties and electrical isolation (except for carbon-filled PEEK) – Excellent resistance to strong energy radiations (gamma and X-rays) – In accordance to EU and FDA directives, concerning materials being in contact to food substances. <p>These features, along with its excellent sterizability through steam, dry heat, ethylen oxide and gamma rays make this product particularly appreciated for medical, pharmaceutical and food applications.</p>
APPLICATION FIELDS	<p>Any fields where high performance polymers are needed</p> <p>in this case the body requires high resistance to chemicals, preparation of polymer application of fasteners, metal tapping, resistance to repeated sterilization cycles, dimensional stability and compatibility of the polymer with the food sector.</p>
SPECIAL NOTES	<p>Cattini Engineering Plastics is recommended by:</p> <p>- VICTREX® : http://victrex.com -</p>