05-09_LEVER PUSHER(PAA_PARA)-ENG.DOC

COCADENTICE ENVENINEERAING PLASTICE	
MOULDED MATERIAL	PARA- IXEF® (polyarylamide+fiberglass)
FAMILY OF MATERIALS	PAA;PPA;PAMXD6;PARA(High Performance Polyamides)
POLYMER'S FEATURES	IXEF® compounds represent a special group of glass fibre and/or mineral reinforced thermoplastics. The basic resin of IXEF® compounds is polyarylamide (aromatic semi-crystall polyamide), which gives good properties to the injected parts used in many industrial applications. Very high stiffness and high resistance to mechanical stress High resistance to buckling Excellent surface finishing Good dimensional stability Low moulding shrinkage and high precision reproducibility, what allows the guarantee of minimum tolerances. Slow and modest water inlet Like all the other polyamides, polyarylamide too is quite sentitive to humidity. Anyway, its semi-aromatic character causes a weaker and slower water inlet o moulded parts containing IXEF® compounds, than PA6 and PA66 parts which more sensitive to humidity.
APPLICATION FIELDS	Automotive and transport Petrol pumps, cover for turnover device, vandal-proof seats, rear view element clutch parts, wiper commands, oil filter boxes, steering lever knee joint for headlights, door handles, seat control drive, headlight parabola, etc. Electrotechnical industry Connectors, racks of electrical and electronic devices, sliding guides for video for recorders, guarded switches, CD disc holder, winding motor brackets, telecommunication parts, etc. Home appliances Iron elements, electric shaver heads, support brackets for vacuum cleaner mot sewing machine elements, etc. Others Applications in the fields of leasure and tools. In the specific case, the lever requires good stiffness and chemical resistance, good surface finish, the polymer must also allow the processing of machine too the assembly of other components in different polymers and metal joints by pressure, and must be compatible with the medical

LEVER PUSHER

CATTINI S.R.L. - via Giuseppe Verdi, 4 - 42018 San Martino in Rio (RE) ITA Tel.: +39 0522 695 220 Fax: +39 0522 695 254 web: <u>http://www.cattini.it</u> Certificata: UNI EN ISO 9001 - UNI EN ISO 14001